



DISCLAIMER: UNIVERSALPEGASUS INTERNATIONAL MAKES NO WARRANTY (EXPRESSED, IMPLIED OR OTHERWISE) THAT THE INFORMATION CONTAINED HEREIN IS ACCURATE OR COMPLETE AS TO ANY AND ALL SUBSURFACE CONDITIONS AND CONFORMATION. ANY RELIANCE CONTRACTOR PLACES ON THE INFORMATION CONTAINED HEREIN AS TO SUCH CONDITIONS, IS DONE SO AT ITS OWN RISK AND EXPENSE. IT IS THE SOLE RESPONSIBILITY OF THE CONTRACTOR TO CONTACT THE STATE "ONE CALL" SYSTEM PRIOR TO ANY EXCAVATION.

SURVEY DATA		STATIONING	
MATCHLINE 1900+00	1900+00 ROAD EDGE 1900+11 CLAR 1361 1900+17 UNNAMED RD 1900+17 ROAD EDGE	MATCHLINE 1950+00	1948+47 FENCE

ENGINEERING DATA		MATERIAL	
REFERENCE DRAWING		51-9K# SBW 11.5 CC	2165'
CLASS LOCATION		5-9K# SBW 11.5 CC	60'
MINIMUM DEPTH OF COVER		11-9K# SBW 11.5 CC	2775'
AC MITIGATION / CATHODIC PROTECTION		4-9K# SBW 11.5 CC	569-7' CCC
			629-7' CCC

ENVIRONMENTAL DATA		STATIONS	
WATERBODY/WETLAND CROSSINGS	W-155	1904+65	1911+30
WATERBODY/WETLAND LENGTH	465'		

BILL OF MATERIALS				MISCELLANEOUS MATERIALS				TYPICAL DRAWINGS		GENERAL INFORMATION		LEGEND		REVISIONS				APPROVALS						
ITEM NO.	QTY	UOM	REQ#	MATERIAL NUMBER	DESCRIPTION	QTY	UOM	REQ#	MATERIAL NUMBER	DESCRIPTION	DWG/FIELD BOOK NO.	TITLE	1. THE MINIMUM DEPTH OF COVER FOR THE PROJECT IS 36 INCHES. ADDITIONAL DEPTH OF COVER IS REQUIRED FOR ROAD AND WATERBODY CROSSINGS, AND IS TO BE IN ACCORDANCE WITH REFERENCED PERMIT DRAWINGS, SITE SPECIFIC DRAWINGS, OR CONSTRUCTION SPECIFICATIONS, WHICHEVER IS MORE STRINGENT.	1	NO.	DESCRIPTION	DATE	REV BY	CHK BY	APP BY	DRAWN BY:	MB	CONSTRUCTION PERMIT NO.	
4	60	FT			36" O.D. x 0.750" W.T., API 5L, X70, PSL2, DSAW, 14-16 MILS FBE & 24-30 MILS ARO	3	EA			SET ON WEIGHTS	21040-510-TYP-20001	CATHODIC PROTECTION STD. SINGLE POINT TEST STATION, TYPE 1	2. THE BOUNDARIES OF ALL WORK AREAS WILL BE CLEARLY MARKED AND ALL WORK SHALL REMAIN WITHIN THE DESIGNATED WORK AREA.	2								CHECKED BY:	MJ	MAINTENANCE OPERATION REGION
5	4940	FT			36" O.D. x 0.625" W.T., API 5L, X70, PSL2, DSAW, 14-16 MILS FBE	8	EA			PIPELINE MARKERS	21040-510-TYP-20002	CATHODIC PROTECTION STD. FOREIGN PIPELINE CROSSING TEST STATION, TYPE 2	3. THE REQUIRED STATE ONE CALL NOTIFICATION IS THE RESPONSIBILITY OF THE CONSTRUCTION CONTRACTOR.	3	1	IFC (UPDATE ENV. RE-ROUTES, FOOT-PRINT)	2016-04-08	MB	MJ	RG		PROJECT MANAGER	RG	MIN. TEST PRESSURE 1816 PSI
FITTINGS SUMMARY				CONTINUOUS CONCRETE COATING				PIPE COATING DATA		SPECIAL NOTES		REVISIONS		APPROVALS										
ITEM NO.	QTY	UOM	REQ#	MATERIAL NUMBER	DESCRIPTION	QTY	UOM	REQ#	MATERIAL NUMBER	DESCRIPTION	21040-510-TYP-20028	TYPICAL OPEN CUT / BORE	4. THE CONTRACTOR SHALL ACCESS THE WORK AREA USING ONLY PUBLIC ROADS AND APPROVED ACCESS ROADS.	4	0	ISSUED FOR CONSTRUCTION	2015-12-15	MB	MJ	RG		PROJECT DEF. NO.		DESIGN PRESSURE 1440 PSI
PIPE ASSEMBLIES				PIPE COATING: 14 MIL MINIMUM FBE AND 24 MIL MINIMUM ARO				TYPICAL PIPELINE MARKER ASSEMBLY		1. INDUCTION BEND QUANTITIES ALONG WITH THEIR DESCRIPTIONS ARE LOCATED ON DRAWING		REVISIONS		APPROVALS										
QTY	UOM	DESCRIPTION	DESCRIPTION	DESCRIPTION	DESCRIPTION	DESCRIPTION	DESCRIPTION	DESCRIPTION	DESCRIPTION	DESCRIPTION	DESCRIPTION	DESCRIPTION	DESCRIPTION	DESCRIPTION	DESCRIPTION	DESCRIPTION	DESCRIPTION	DESCRIPTION	DESCRIPTION	DESCRIPTION	DESCRIPTION	DESCRIPTION	DESCRIPTION	DESCRIPTION